



Product Service

CERTIFICATE

No. Z2 118443 0038 Rev. 05

Holder of Certificate: **Jinko Solar Co., Ltd.**
No.1, Yingbin Road, Economic Development Zone
334100 Shangrao City, Jiangxi
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:



Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062307436-05

Valid until: 2029-08-15

Date, 2024-08-26

(Zhulin Zhang)

CERTIFICATE

No. Z2 118443 0038 Rev. 05

Model(s):

1500VDC system voltage:

JKMxxxM-72HL4-TV (xxx=530-545, in steps of 5)
JKMxxxM-72HL4-V, JKMxxxM-72HL4-V-J (xxx=540-570, in steps of 5)
JKMxxxM-54HL4-V (xxx=405-425, in steps of 5)
JKMxxxN-78HL4-V, JKMxxxN-78HL4-V-J (xxx=605-650, in steps of 5)
JKMxxxN-72HL4-V, JKMxxxN-72HL4-V-J, JKBWxxxN-72HL4-V,
JKMxxxN-72HL4-V-L (xxx=560-615, in steps of 5)
JKMxxxN-60HL4-V, JKMxxxN-60HL4-V-J (xxx=470-510, in steps of 5)
JKMxxxN-54HL4-V, JKMxxxN-54HL4R-V, JKBWxxxN-54HL4R-V
(xxx=420-460, in steps of 5)
JKMxxxN-66HL4M-V, JKMxxxN-66HL4M-V-L
(xxx=600-640, in steps of 5)

1000VDC system voltage:

JKMxxxM-72HL4, JKMxxxM-72HL4-J (xxx=540-570, in steps of 5)
JKMxxxM-54HL4 (xxx=405-425, in steps of 5)
JKMxxxN-78HL4, JKMxxxN-78HL4-J (xxx=605-650, in steps of 5)
JKMxxxN-72HL4, JKMxxxN-72HL4-J, JKBWxxxN-72HL4, JKMxxxN-
72HL4-L (xxx=560-615, in steps of 5)
JKMxxxN-60HL4, JKMxxxN-60HL4-J (xxx=470-510, in steps of 5)
JKMxxxN-54HL4, JKMxxxN-54HL4R (xxx=420-460, in steps of 5)
JKMxxxN-66HL4M (xxx=600-640, in steps of 5)
JKMxxxN-54HL4-B, JKMxxxN-54HL4R-B (xxx=420-460, in steps of 5)
xxx is standing for rated output power at STC

Parameters:

Fire Safety Class:	Class C according to UL790
Safety Class:	Class II
Max. System Voltage:	1500V DC or 1000V DC
Construction:	Framed with Junction box, cable and connector.

Production

Facility(ies):

074043, 105416, 115863, 115864, 115876
115862, 116025, 119488, 075612, 121280,
115860, 118443, 122742, 118612, 119487,
125355

Tested according to:

IEC 61215-1:2021
IEC 61215-1-1:2021
IEC 61215-2:2021
IEC 61730-1:2023
IEC 61730-2:2023
EN 61215-1:2021
EN 61215-1-1:2021
EN 61215-2:2021
EN IEC 61730-1:2018
EN IEC 61730-1:2018/AC:2018-06
EN IEC 61730-2:2018
EN IEC 61730-2:2018/AC:2018-06